

	Type	L #	Hits	Search Text	DBs
1	BRS	L1	7078	((determin\$5 or detect\$5 or measur\$5 or test\$5 or monitor\$5 or inspect\$5) near6 (ber or (bit near2 error near2 rate)))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
2	BRS	L2	58594	gui or (graphic\$2 near3 user near3 interface)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
3	BRS	L3	384264	controller and memory	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
4	BRS	L5	263	((determin\$5 or detect\$5 or measur\$5 or test\$5 or monitor\$5 or inspect\$5) near6 (ber or (bit near2 error near2 rate))) with (dut or (device near3 under near3 test) or fiber or waveguide or cable)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
5	BRS	L6	3	5 and 2 and 3 and @ad<="20010423"	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
6	BRS	L7	36	4 and optic\$2	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
7	BRS	L8	3	5 and 2 and memory and @ad<="20010423"	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
8	BRS	L9	3	5 and 2 and @ad<="20010423"	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
9	BRS	L10	8	5 and 2 and memory	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
10	BRS	L11	10	5 and 2	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
11	BRS	L4	50	1 and 2 and 3 and @ad<="20010423"	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB